

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (currently amended) A server for use with and separable from a brewer for retaining and dispensing beverages, the server comprising:
  - a housing;
  - a reservoir positioned in the housing for retaining a beverage;
  - a heater carried in the server and attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir; and
  - means for controllably adding energy to the reservoir to preheat the reservoir before depositing beverage into the reservoir.
2. (original) The server of claim 1 further comprising the server in combination with a beverage brewer.
3. (original) The server of claim 1 further comprising the server in combination with a dispensing station.
4. (original) The server of claim 1 further comprising a space defined between at least a portion of an inside surface of the housing and at least a portion of an outside surface of the reservoir, the space providing a thermal barrier between the outside of the reservoir and an outside of the housing.
5. (original) The server of claim 4 further comprising insulating material being positioned in the space defined between at least a portion of an inside surface of the housing and at least a portion of an outside surface of the reservoir to provide a thermal barrier between the outside of the reservoir and an outside of the housing.

6. (currently amended) A method of preheating a reservoir in a beverage server for use with and separable from a brewer, the method comprising the steps of:

- providing a server with a reservoir for retaining a beverage;
- providing a passage in the server communicating with the reservoir;
- providing a heater carried in the server attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir;
- providing a controller coupled to the heater for controllably adding energy to the reservoir;
- preheating the reservoir before dispensing beverage to the reservoir; and
- dispensing beverage into the preheated reservoir.

7. (currently amended) A method of preheating a reservoir in a beverage server for use with and separable from a brewer to prevent a decrease in the temperature of a beverage upon being dispensed into the reservoir, the method comprising the steps of:

- providing a server with a reservoir for retaining a beverage;
- providing a passage in the server communicating with the reservoir;
- providing a heater carried in the server and attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir;
- providing a controller coupled to the heater for controlling the heating of the reservoir;
- activating the heater for transferring energy to the reservoir to heat the reservoir before dispensing beverage to the reservoir to prevent a decrease in the temperature of beverage dispensed into the reservoir; and
- dispensing beverage into the preheated reservoir of the server.

8. (original) The method of claim 7 further comprising the step of adding energy to the reservoir prior to dispensing beverage into the reservoir and continuing to add energy to the reservoir after the start of dispensing beverage to the reservoir.

9. (original) The method of claim 8 further comprising the step of terminating the heating of the reservoir after a predetermined time.

10. (original) The method of claim 8 further comprising the steps of terminating the heating of the reservoir after a predetermined time and activating the heater after a second period of time.

11. (original) The method of claim 10 further comprising the steps of repeatedly terminating the heating of the reservoir after a predetermined time and activating the heater after a second period of time for a predetermined number of terminating and activating cycles.

12. (original) The method of claim 8 further comprising the step of terminating the heating of the reservoir after achieving a temperature within a predetermined temperature range.

13. (original) The method of claim 7 further comprising the step of adding energy to at least one of the reservoir and the air in the reservoir prior to dispensing beverage into the reservoir.

14. (original) The method of claim 7 further comprising the steps of:  
providing a heating coil positioned on an outside surface of the reservoir;  
heating the corresponding surface of the reservoir; and  
transferring heat to the reservoir for controllably preheating the reservoir and for controllably heating a beverage to be dispensed therein.

15. (currently amended) A method of reducing the transfer of heat from a beverage to a reservoir in a server into which the beverage is dispensed, the server being of the type for use with and separable from a brewer, the method comprising the steps of:

- providing a server with a reservoir for retaining a beverage;
- providing a passage in the server communicating with the reservoir;
- providing a heater carried in the server attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir;
- providing a controller coupled to the heater for controlling the heating of the reservoir;

- activating the heater for providing energy to the reservoir to heat the reservoir before dispensing beverage to the reservoir to prevent a decrease in the temperature of beverage dispensed into the reservoir;

- preheating the reservoir before dispensing beverage to the reservoir; and
- dispensing beverage into the heated reservoir.

16. (currently amended) A server in combination with and separable from a beverage brewer comprising:

- a beverage brewer for combining heated water with a beverage brewing substance for producing a brewed beverage therefrom;

- a server housing;

- a reservoir positioned in the server housing for retaining a beverage;

- a heater carried in the server and attached to the outside bottom surface of the reservoir for transferring energy from the heater to a beverage retained in the reservoir;

- a controller for controlling operation of the heater; whereby the heater is operated before dispensing beverage to the reservoir for preheating the reservoir before dispensing of beverage therein.

17. (currently amended) A server in combination with and separable from a dispensing station comprising:

- a server housing;
- a reservoir positioned in the server housing for retaining a beverage;
- a heater carried in the server and attached to the outside bottom surface of the reservoir for transferring energy from the heater to a beverage retained in the reservoir;
- a dispensing station for receiving at least one server thereon;
- a controller programmed for preheating the reservoir before depositing beverage therein.

18. (currently amended) A method of maintaining the freshness of beverage retained in a server for use with and separable from a brewer, the method comprising the steps of:

- providing a server with a reservoir for retaining a beverage;
- providing a passage in the server communicating with the reservoir;
- providing a heater carried in the server attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir;
- providing a controller coupled to the heater for controlling the heating of the reservoir;
- activating the heater for providing energy to the reservoir to heat the reservoir before dispensing beverage to the reservoir to prevent a decrease in the temperature of beverage when the beverage is dispensed into the reservoir;
- preheating the reservoir before dispensing beverage to the reservoir;
- dispensing beverage into the heated reservoir; and
- terminating the heating of the reservoir after at least one of a predetermined time and achieving a temperature within a predetermined temperature range.

19. (currently amended) A method of brewing a beverage comprising:
- providing a beverage brewer for combining heated water with a beverage brewing substance for producing a brewed beverage;
  - providing a server with a reservoir for retaining a beverage;
  - providing a passage in the server communicating with the reservoir;
  - providing a heater carried in the server and attached to the outside bottom surface of the reservoir for transferring energy from the heater to the reservoir;
  - providing a controller coupled to the heater for controlling the heating of the reservoir;
  - positioning the server in position relative to the beverage brewer, but removable from the brewer, for receiving a beverage produced by the beverage brewer;
  - initiating a brewing cycle;
  - activating the heater for preheating the server;
  - terminating operation of the heater after at least one of a predetermined time and achieving a temperature within a predetermined temperature range; and
  - dispensing beverage from the brewer into the reservoir of the preheated server through the passage communicating with the reservoir.
20. (previously presented) The method of claim 18 wherein the reservoir is empty prior to the step of preheating the reservoir.